



# 2017 TIRE CATALOG

HOUSTON, TX • 77029 • 8999 MARKET STREET ROAD	• PHONE: 713-673-5588 FAX: 713-673-5578
IRWINDALE, CA • 91706 • 4818 FOURTH STREET	• PHONE: 323-622-1920 FAX: 323-622-1927
NORCROSS, GA • 30071 • 6485 CRESCENT DRIVE, 'E	• PHONE: 678-373-0311 FAX: 678-373-0312
CRANBURY, NJ • 08512 • 2 CAPITAL DRIVE '202	• PHONE: 609-860-0612 FAX: 609-860-2615
MEMPHIS, TN • 38106 • 2365 TEXAS DRIVE	• PHONE: 901-347-2526 FAX: 901-347-2587

[www.horizontire.com](http://www.horizontire.com)







## L-GRIP 16

- "Shark Fin" Tread Pattern.
- Small Knurl Design eliminates the pumping generated which reduces the driving noise.
- The horizontal steps reduce the noise and improve the higher rigidity.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
PCR-3302-YL	155/70R13	STD	75T	BSW	853	4.50B	6.2	21.6	44	9	420 A A
PCR-3304-YL	165/65R13	STD	77T	BSW	908	5.00B	6.7	21.4	44	9	420 A A
PCR-3305-YL	165/70R13	STD	79T	BSW	964	5.00B	6.7	22.1	44	9	420 A A
PCR-3307-YL	175/60R13	STD	77T	BSW	908	5J	7.0	21.3	44	9	420 A A
PCR-3308-YL	175/70R13	STD	82T	BSW	1047	5.00B	7.0	22.7	44	9	420 A A
PCR-3309-YL	185/70R13	STD	86T	BSW	1169	5.50B	7.4	23.2	44	10	420 A A
PCR-3403-YL	175/65R14	STD	82T	BSW	1047	5J	7.0	23.0	44	10	420 A A
PCR-3404-YL	175/70R14	STD	84T	BSW	1103	5J	7.0	23.7	44	10	420 A A
PCR-3405-YL	185/60R14	STD	82H	BSW	1047	5 1/2J	7.4	22.8	44	9	420 A A
PCR-3406-YL	185/65R14	STD	86T	BSW	1169	5 1/2J	7.4	23.5	44	9	420 A A
PCR-3407-YL	185/70R14	STD	88T	BSW	1235	5 1/2J	7.4	24.3	44	10	420 A A
PCR-3408-YL	195/60R14	STD	86T	BSW	1169	6J	7.9	23.2	44	10	420 A A
PCR-3409-YL	195/70R14	STD	91T	BSW	1356	6J	7.9	24.8	44	10	420 A A
PCR-3410-YL	205/60R14	STD	88T	BSW	1235	6J	8.2	23.7	44	9	420 A A
PCR-3411-YL	205/70R14	XL	98T	BSW	1654	6J	8.2	25.4	49	10	420 A A
PCR-3503-YL	205/70R15	STD	96T	BSW	1566	6J	8.2	26.3	44	10	420 A A

## L-ZEAL 56

- Big block design on the shoulder improves high speed performance.
- The strong rib improves the driving stability.
- Four straight grooves improve drainage.
- Small lug design reduces the noise and enhances the gripping power on wet ground.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
UHP-3623-YL	205/50R16	XL	91W	BSW	1356	6 1/2J	8.4	24.1	49	10	300 A A
UHP-3625-YL	215/55R16	STD	93W	BSW	1433	7J	8.9	25.3	44	10	300 A A
UHP-3627-YL	225/55R16	XL	99W	BSW	1709	7J	9.2	25.7	49	10	300 A A
UHP-3717-YL	205/40R17	XL	84W	BSW	1103	7 1/2J	8.3	23.5	49	10	300 A A
UHP-3718-YL	205/45R17	STD	84W	BSW	1103	7J	8.1	24.3	44	10	300 A A
UHP-3708-YL	205/50R17	XL	93W	BSW	1433	6 1/2J	8.4	25.1	49	10	300 A A
UHP-3719-YL	215/40R17	STD	83W	BSW	1074	7 1/2J	8.6	23.8	44	10	300 A A
UHP-3709-YL	215/45R17	XL	91W	BSW	1356	7J	8.4	24.6	49	10	300 A A
UHP-3720-YL	215/50R17	XL	95W	BSW	1521	7J	8.9	25.5	49	10	300 A A
UHP-3711-YL	225/45R17	XL	94W	BSW	1477	7 1/2J	8.9	25.0	49	10	300 A A
UHP-3712-YL	225/50R17	STD	94W	BSW	1477	7J	9.2	25.9	44	10	300 A A
UHP-3714-YL	225/55R17	STD	97V	BSW	1610	7J	9.2	26.8	44	10	300 A A
UHP-3715-YL	235/45R17	XL	97W	BSW	1610	8J	9.3	25.4	49	10	300 A A
UHP-3716-YL	235/55R17	STD	99V	BSW	1709	7 1/2J	9.6	27.2	44	10	300 A A
UHP-3809-YL	215/40R18	XL	89W	BSW	1279	7 1/2J	8.6	24.8	49	10	300 A A
UHP-3810-YL	215/45R18	XL	93W	BSW	1433	7J	8.4	25.6	49	10	300 A A
UHP-3803-YL	225/40R18	XL	92W	BSW	1389	8J	9.1	25.1	49	10	300 A A
UHP-3804-YL	225/45R18	XL	95W	BSW	1521	7 1/2J	8.9	25.9	49	10	300 A A
UHP-3805-YL	235/40R18	XL	95W	BSW	1521	8 1/2J	9.5	25.4	49	10	300 A A
UHP-3806-YL	245/40R18	XL	97W	BSW	1610	8 1/2J	9.8	25.7	49	10	300 A A
UHP-3807-YL	245/45R18	XL	100W	BSW	1764	8J	9.6	26.7	49	10	300 A A
UHP-3808-YL	255/55R18	STD	105V	BSW	2040	8J	10.4	29.0	44	10	300 A A
UHP-3903-YL	225/35R19	STD	84W	BSW	1103	8J	9.1	25.2	44	10	300 A A
UHP-3901-YL	235/35R19	XL	91W	BSW	1356	8 1/2J	9.5	25.5	49	10	300 A A
UHP-3905-YL	235/45R19	STD	95W	BSW	1521	8J	9.3	27.4	44	10	300 A A
UHP-3902-YL	245/35R19	XL	93W	BSW	1433	8 1/2J	9.8	25.8	49	10	300 A A
UHP-3906-YL	245/45R19	STD	98W	BSW	1654	8J	9.6	27.7	44	10	300 A A
UHP-3904-YL	255/35R19	XL	96W	BSW	1566	9J	10.2	26.0	49	10	300 A A
UHP-3907-YL	255/45R19	STD	100W	BSW	1764	8 1/2J	10.0	28.1	44	10	300 A A
UHP-3908-YL	255/50R19	STD	103V	BSW	1929	8J	10.4	29.1	44	10	300 A A
UHP-3002-YL	225/35R20	XL	90W	BSW	1323	8J	9.1	26.2	49	10	300 A A
UHP-3003-YL	235/35R20	XL	92W	BSW	1389	8 1/2J	9.5	26.5	49	10	300 A A
UHP-3001-YL	245/35R20	XL	95W	BSW	1521	8 1/2J	9.8	26.8	49	10	300 A A
UHP-3004-YL	255/35R20	XL	97W	BSW	1610	9J	10.2	27.0	49	10	300 A A





## L-COMFORT 68

- The open horizontal grooves improve drainage.
- The ventilation holes on shoulder enhance the driving safety.
- The discontinuous central rib and high-strength deflection zone reduce the heat generation.



## L-FINDER 78

- Wide and deep design on the shoulder enhances the gripping power and heat release.
- Precise spacing and angle block design reduce the noise.
- Four straight grooves improve drainage.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
PCR-3505-YL	185/55R15	STD	82V	BSW	1047	6J	7.6	23.0	44	10	380 A A
PCR-3506-YL	185/60R15	STD	84H	BSW	1103	5 1/2J	7.4	23.7	44	10	380 A A
PCR-3507-YL	185/65R15	STD	88H	BSW	1235	5 1/2J	7.4	24.4	44	10	380 A A
PCR-3509-YL	195/50R15	STD	82V	BSW	1047	6J	7.9	22.7	44	10	380 A A
PCR-3510-YL	195/55R15	STD	85V	BSW	1136	6J	7.9	23.4	44	10	380 A A
PCR-3511-YL	195/60R15	STD	88V	BSW	1235	6J	7.9	24.2	44	10	380 A A
PCR-3514-YL	195/65R15	STD	91H	BSW	1356	6J	7.9	25.0	44	9	380 A A
PCR-3521-YL	195/65R15	STD	91V	BSW	1356	6J	7.9	25.0	44	9	380 A A
PCR-3515-YL	205/60R15	STD	91H	BSW	1356	6J	8.2	24.7	44	10	380 A A
PCR-3522-YL	205/60R15	STD	91V	BSW	1356	6J	8.2	24.7	44	10	380 A A
PCR-3516-YL	205/65R15	STD	94V	BSW	1477	6J	8.2	25.5	44	10	380 A A
PCR-3517-YL	215/65R15	STD	96V	BSW	1566	6 1/2J	8.7	26.0	44	10	380 A A
PCR-3519-YL	215/70R15	STD	98T	BSW	1654	6 1/2J	8.7	26.9	44	10	380 A A
PCR-3520-YL	235/70R15	STD	103T	BSW	1896	7J	9.4	28.0	44	12	380 A A
PCR-3611-YL	185/50R16	STD	81V	BSW	1019	6J	7.6	23.3	44	9	380 A A
PCR-3612-YL	195/55R16	STD	87V	BSW	1202	6J	7.9	24.4	44	10	380 A A
PCR-3613-YL	205/55R16	STD	91V	BSW	1356	6 1/2J	8.4	24.9	44	10	380 A A
PCR-3614-YL	205/60R16	STD	92V	BSW	1389	6J	8.2	25.7	44	10	380 A A
PCR-3615-YL	205/65R16	STD	95T	BSW	1521	6J	8.2	26.5	44	10	380 A A
PCR-3617-YL	215/60R16	XL	99V	BSW	1709	6 1/2J	8.7	26.1	49	10	380 A A
PCR-3618-YL	215/65R16	STD	98H	BSW	1654	6 1/2J	8.7	27.0	44	10	380 A A
PCR-3619-YL	225/60R16	STD	98V	BSW	1654	6 1/2J	9.0	26.6	44	10	380 A A
PCR-3620-YL	225/65R16	STD	100T	BSW	1764	6 1/2J	9.0	27.5	44	10	380 A A
PCR-3621-YL	235/60R16	STD	100H	BSW	1764	7J	9.4	27.1	44	11	380 A A
PCR-3622-YL	235/65R16	STD	103T	BSW	1929	7J	9.4	28.0	44	11	380 A A
PCR-3707-YL	215/55R17	STD	94V	BSW	1477	7J	8.9	26.3	44	10	380 A A

Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
PCR-3501-YL	P215/75R15	STD	100T	BSW	1764	6J	8.5	27.7	44	11	420 A A
PCR-3502-YL	P235/75R15	STD	105T	BSW	2048	6 1/2J	9.3	28.9	44	11	420 A A
PCR-3601-YL	P215/70R16	STD	99T	BSW	1709	6 1/2J	8.7	27.9	44	11	420 A A
PCR-3602-YL	P225/70R16	STD	101T	BSW	1819	6 1/2J	9.0	28.4	44	11	420 A A
PCR-3603-YL	P225/75R16	STD	104T	BSW	1985	6J	8.8	29.3	44	11	420 A A
PCR-3604-YL	P235/70R16	STD	104T	BSW	2150	7J	9.4	29.0	49	11	420 A A
PCR-3606-YL	P235/75R16	XL	109T	BSW	2095	6 1/2J	9.3	29.8	49	11	420 A A
PCR-3607-YL	P245/70R16	STD	106T	BSW	2095	7J	9.8	29.5	44	11	420 A A
PCR-3608-YL	P255/65R16	STD	106T	BSW	2095	7 1/2J	10.2	29.1	44	11	420 A A
PCR-3609-YL	P255/70R16	STD	109T	BSW	2271	7 1/2J	10.2	30.1	44	11	420 A A
PCR-3610-YL	P265/70R16	STD	111T	BSW	2403	8J	10.7	30.6	44	11	420 A A
PCR-3701-YL	P225/65R17	STD	102T	BSW	1764	6 1/2J	9.0	28.5	44	11	420 A A
PCR-3702-YL	P235/60R17	STD	100T	BSW	1764	7J	9.4	28.1	44	11	420 A A
PCR-3703-YL	P235/65R17	STD	103T	BSW	1929	7J	9.4	29.1	44	11	420 A A
PCR-3704-YL	P245/65R17	STD	105T	BSW	2040	7J	9.8	29.5	44	11	420 A A
PCR-3705-YL	P265/65R17	STD	110T	BSW	2337	8J	10.7	30.6	44	11	420 A A
PCR-3706-YL	P265/70R17	STD	113T	BSW	2536	8J	10.7	31.7	44	11	420 A A
PCR-3801-YL	P235/60R18	STD	102T	BSW	1874	7J	9.4	29.1	44	11	420 A A
PCR-3802-YL	P235/65R18	STD	104T	BSW	1985	7J	9.4	30.0	44	11	420 A A
LTR-3501-YL	31X10.50R15LT	C	109Q	BSW	2271	8 1/2J	10.6	30.5	51	13	-
LTR-3601-YL	LT215/85R16	E	115/112Q	BSW	2679/2470	6J	8.5	30.4	80	13	-
LTR-3602-YL	LT225/75R16	E	115/112Q	BSW	2679/2470	6J	8.8	29.3	80	13	-
LTR-3603-YL	LT235/85R16	E	120/116Q	BSW	3043/2778	6 1/2J	9.3	31.7	80	13	-
LTR-3604-YL	LT245/75R16	E	120/116Q	BSW	3043/2778	7J	9.8	30.5	80	13	-
LTR-3605-YL	LT265/75R16	E	123/120Q	BSW	3418/3087	7 1/2J	10.5	31.7	80	13	-
LTR-3701-YL	LT235/80R17	E	120/117Q	BSW	3087/2833	6 1/2J	9.3	31.8	80	13	-
LTR-3702-YL	LT245/70R17	E	119/116Q	BSW	2999/2756	7J	9.8	30.6	80	13	-
LTR-3703-YL	LT245/75R17	E	121/118Q	BSW	3197/2911	7J	9.8	31.5	80	13	-
LTR-3704-YL	LT265/70R17	E	121/118Q	BSW	3197/2911	8J	10.7	31.7	80	13	-



# COLO H01

- Developed for middle class passenger cars.
- Fully considering the drive and ride comfort.
- Both economy and environmental protection issues were considered.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
PCR-3417-YL	185/65R14	STD	86H	BSW	1168	5 1/2J	7.44	23.46	44	10	420 A A
PCR-3415-YL	185/70R14	STD	88H	BSW	1235	5 1/2J	7.44	24.25	44	10	420 A A
PCR-3416-YL	195/60R14	STD	86H	BSW	1168	6J	7.91	20.04	44	10	420 A A
PCR-3418-YL	195/65R14	STD	90H	BSW	1279	6J	7.91	24.02	44	10	420 A A
PCR-3419-YL	195/70R14	STD	91H	BSW	1356	6J	7.91	24.80	44	10	420 A A
PCR-3420-YL	205/60R14	STD	88H	BSW	1235	6J	8.23	23.70	44	10	420 A A
PCR-3421-YL	205/70R14	STD	95H	BSW	1521	6J	8.23	25.35	44	10	420 A A
PCR-3422-YL	215/70R14	STD	96H	BSW	1565	6 1/2J	8.70	25.91	44	10	420 A A
PCR-3527-YL	185/55R15	STD	82V	BSW	1047	5 1/2J	7.64	23.03	44	10	420 A A
PCR-3528-YL	185/60R15	XL	88H	BSW	1235	5 1/2J	7.44	23.74	50	10	420 A A
PCR-3523-YL	185/65R15	STD	88H	BSW	1235	5 1/2J	7.44	24.45	44	10	420 A A
PCR-3524-YL	185/65R15	STD	88T	BSW	1235	5 1/2J	7.44	24.45	44	10	420 A A
PCR-3525-YL	195/50R15	STD	82V	BSW	1047	6J	7.91	22.72	44	10	420 A A
PCR-3529-YL	195/55R15	STD	85V	BSW	1135	6J	7.91	23.43	44	10	420 A A
PCR-3530-YL	195/60R15	STD	88H	BSW	1235	6J	7.91	24.21	44	10	420 A A
PCR-3531-YL	195/65R15	STD	91H	BSW	1356	6J	7.91	25.00	44	10	420 A A
PCR-3532-YL	205/60R15	STD	91V	BSW	1356	6J	8.23	24.69	44	10	420 A A
PCR-3537-YL	205/65R15	STD	94H	BSW	1477	6J	8.23	25.47	44	10	420 A A
PCR-3526-YL	205/70R15	STD	96H	BSW	1565	6J	8.23	26.34	44	10	420 A A
PCR-3533-YL	215/60R15	STD	94H	BSW	1477	6 1/2J	8.70	25.16	44	10	420 A A
PCR-3534-YL	215/65R15	STD	96H	BSW	1565	6 1/2J	8.70	26.02	44	10	420 A A
PCR-3535-YL	215/70R15	STD	98H	BSW	1653	6 1/2J	8.70	26.89	44	10	420 A A
PCR-3536-YL	225/60R15	STD	96V	BSW	1565	6 1/2J	8.98	25.63	44	10	420 A A
PCR-3624-YL	205/55R16	STD	91V	BSW	1356	6 1/2J	8.43	24.88	44	10	420 A A
PCR-3623-YL	205/55R16	STD	91H	BSW	1356	6 1/2J	8.43	24.88	44	10	420 A A
PCR-3625-YL	205/60R16	STD	92V	BSW	1389	6J	8.23	25.67	44	10	420 A A
PCR-3629-YL	205/65R16	STD	95H	BSW	1521	6J	8.23	24.69	44	10	420 A A
PCR-3630-YL	215/55R16	STD	93V	BSW	1433	7J	8.90	25.28	44	10	420 A A
PCR-3627-YL	215/60R16	XL	99H	BSW	1709	6 1/2J	8.70	26.14	50	10	420 A A
PCR-3637-YL	215/60R16	STD	95V	BSW	1521	6 1/2J	8.70	26.14	44	10	420 A A
PCR-3631-YL	215/65R16	STD	98H	BSW	1653	6 1/2J	8.70	27.01	44	10	420 A A
PCR-3632-YL	225/55R16	STD	95V	BSW	1521	7J	9.17	25.75	44	10	420 A A
PCR-3626-YL	225/60R16	STD	98H	BSW	1653	6 1/2J	8.98	26.61	44	10	420 A A
PCR-3633-YL	235/60R16	STD	100H	BSW	1764	7J	9.45	27.09	44	10	420 A A
PCR-3724-YL	215/55R17	STD	94V	BSW	1477	7J	8.90	26.30	44	10	420 A A
PCR-3725-YL	225/55R17	XL	101H	BSW	1819	7J	9.17	26.77	50	10	420 A A

# ENRI U08

- Developed for middle-high class passenger cars.
- Fully considering the drive and ride comfort.
- Asymmetric pattern design improves the handling performance on both dry and wet ground.
- The countless lines on the groove wall reduce the noise efficiently.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
UHP-3630-YL	205/45R16	XL	87W	BSW	1201	7J	8.11	23.23	50	10	400 A A
UHP-3628-YL	205/50R16	XL	91W	BSW	1356	6 1/2J	8.43	24.09	50	10	400 A A
UHP-3629-YL	205/55R16	XL	94W	BSW	1477	6 1/2J	8.43	24.88	50	10	400 A A
UHP-3608-YL	225/55R16	XL	99W	BSW	1709	7J	9.17	25.75	50	10	400 A A
UHP-3721-YL	205/40R17	XL	84W	BSW	1102	7 1/2J	8.35	23.46	50	10	400 A A
UHP-3722-YL	205/45R17	XL	88W	BSW	1235	7J	8.11	24.25	50	10	400 A A
UHP-3726-YL	205/50R17	XL	93W	BSW	1433	6 1/2J	8.43	25.12	50	10	400 A A
UHP-3723-YL	215/45R17	XL	91W	BSW	1356	7J	8.39	24.65	50	10	400 A A
UHP-3704-YL	215/50R17	XL	95W	BSW	1521	7J	8.90	25.51	50	10	400 A A
UHP-3705-YL	215/55R17	XL	98W	BSW	1653	7J	8.90	26.30	50	10	400 A A
UHP-3728-YL	225/45R17	XL	94W	BSW	1477	7 1/2J	8.86	24.96	50	10	400 A A
UHP-3706-YL	225/50R17	XL	98W	BSW	1653	7J	9.17	25.91	50	10	400 A A
UHP-3707-YL	225/55R17	XL	101W	BSW	1819	7J	9.17	26.77	50	10	400 A A
UHP-3727-YL	235/45R17	XL	97W	BSW	1609	8J	9.29	25.35	50	10	400 A A
UHP-3729-YL	235/50R17	XL	100V	BSW	1764	7 1/2J	9.65	26.30	50	10	400 A A
UHP-3730-YL	245/40R17	XL	95W	BSW	1521	8 1/2J	9.76	24.72	50	10	400 A A
UHP-3731-YL	245/45R17	XL	99W	BSW	1709	8J	9.57	25.67	50	10	400 A A
UHP-3811-YL	225/40R18	XL	92W	BSW	1389	8J	9.06	25.08	50	10	400 A A
UHP-3812-YL	225/45R18	XL	95W	BSW	1521	7 1/2J	8.86	25.94	50	10	400 A A
UHP-3819-YL	225/55R18	XL	102V	BSW	1874	7J	9.17	27.76	50	10	400 A A
UHP-3813-YL	235/40R18	XL	95W	BSW	1521	8 1/2J	9.49	25.39	50	10	400 A A
UHP-3816-YL	235/45R18	XL	98W	BSW	1653	8J	9.29	26.34	50	10	400 A A
UHP-3817-YL	235/50R18	XL	101W	BSW	1819	7 1/2J	9.65	27.28	50	10	400 A A
UHP-3814-YL	245/40R18	XL	97W	BSW	1609	8 1/2J	9.76	25.71	50	10	400 A A
UHP-3815-YL	245/45R18	XL	100W	BSW	1764	8J	9.57	26.65	50	10	400 A A
UHP-3818-YL	245/50R18	XL	104W	BSW	1984	7 1/2J	9.96	27.68	50	10	400 A A
UHP-3909-YL	245/45R19	XL	102W	BSW	1874	8J	9.57	27.68	50	10	400 A A
UHP-3209-YL	275/30R20	XL	97W	BSW	1609	9 1/2J	10.94	26.54	50	10	400 A A
UHP-3220-YL	235/30R22	XL	90W	BSW	1323	8 1/2J	9.49	27.60	50	10	400 A A
UHP-3221-YL	245/30R22	XL	92W	BSW	1389	8 1/2J	9.76	27.83	50	10	400 A A
UHP-3222-YL	255/30R22	XL	95W	BSW	1521	9J	10.24	28.07	50	10	400 A A





## MAGA A/T ONE

- Design for urban SUV.
- Wear resistant compound inside.
- 3D sipes on tread to enhance the gripping power.
- All season pattern design.

Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
SUV-3501-AT-YL	235/75R15	XL	109S	BSW	2271	6 1/2J	9.25	28.86	50	13	500 A B
SUV-3601-AT-YL	235/70R16	STD	106T	BSW	2094	7J	9.45	28.98	44	13	500 A B
SUV-3602-AT-YL	245/70R16	STD	107T	BSW	2149	7J	9.76	29.53	44	13	500 A B
SUV-3603-AT-YL	265/70R16	STD	112T	BSW	2469	8J	10.71	30.63	44	13	500 A B
SUV-3701-AT-YL	235/65R17	STD	104T	BSW	1984	7J	9.45	29.06	44	13	500 A B
SUV-3702-AT-YL	245/65R17	STD	107S	BSW	2149	7J	9.76	29.53	44	13	500 A B
SUV-3703-AT-YL	265/70R17	STD	115S	BSW	2679	8J	10.71	31.65	44	13	500 A B
LTR-3501-AT-YL	31x10.50R15LT	C	109S	BSW	2271	8 1/2J	10.54	30.52	51	16	500 A B
LTR-3601-AT-YL	LT225/75R16	E	115/112Q	BSW	2679/2469	6J	8.78	29.29	80	13	500 A B
LTR-3602-AT-YL	LT235/85R16	E	120/116S	BSW	3086/2756	6 1/2J	9.25	31.73	80	13	500 A B
LTR-3602A-AT-YL	LT235/85R16	E	120/116Q	BSW	3086/2756	6 1/2J	9.25	31.73	80	13	500 A B
LTR-3603-AT-YL	LT245/75R16	E	120/116S	BSW	3042/2778	7J	9.76	30.47	80	13	500 A B
LTR-3603A-AT-YL	LT245/75R16	E	120/116Q	BSW	3042/2778	7J	9.76	30.47	80	13	500 A B
LTR-3701-AT-YL	LT265/70R17	E	121/118R	BSW	2679/2472	8J	10.71	31.65	80	13	500 A B
SUV-3503-AT-YL	205/75R15	STD	97T	BSW	1609	5 1/2J	7.99	27.13	44	13	500 A B
SUV-3504-AT-YL	215/75R15	STD	100S	BSW	1764	6J	8.50	27.68	44	13	500 A B
SUV-3505-AT-YL	225/70R15	STD	100S	BSW	1764	6 1/2J	8.98	27.44	44	13	500 A B
SUV-3506-AT-YL	225/75R15	STD	102S	BSW	1874	6J	8.78	28.31	44	13	500 A B
SUV-3507-AT-YL	255/70R15	STD	108T	BSW	2205	7 1/2J	10.24	29.09	44	13	500 A B
SUV-3508-AT-YL	265/70R15	STD	112S	BSW	2469	8J	10.71	29.65	44	13	500 A B
SUV-3604-AT-YL	215/65R16	STD	98T	BSW	1653	6 1/2J	8.70	27.01	44	13	500 A B
SUV-3605-AT-YL	215/70R16	STD	100T	BSW	1764	6 1/2J	8.70	27.87	44	13	500 A B
SUV-3606-AT-YL	235/60R16	XL	104H	BSW	1984	7J	9.45	27.09	50	13	500 A B
SUV-3607-AT-YL	255/65R16	STD	109T	BSW	2271	7 1/2J	10.24	29.06	44	13	500 A B
SUV-3608-AT-YL	255/70R16	STD	111T	BSW	2403	7 1/2J	10.24	30.08	44	13	500 A B
SUV-3704-AT-YL	225/65R17	STD	102T	BSW	1874	6 1/2J	8.98	28.50	44	13	500 A B
SUV-3705-AT-YL	245/70R17	STD	110S	BSW	2337	7J	9.76	30.55	44	13	500 A B
SUV-3706-AT-YL	255/65R17	STD	110H	BSW	2337	7 1/2J	10.24	30.08	44	13	500 A B
SUV-3707-AT-YL	255/70R17	STD	112S	BSW	2469	7 1/2J	10.24	31.10	44	13	500 A B

Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
SUV-3708-AT-YL	265/65R17	STD	112T	BSW	2469	8J	10.71	30.55	44	13	500 A B
SUV-3709-AT-YL	275/65R17	STD	115T	BSW	2679	8J	10.98	31.10	44	13	500 A B
SUV-3801-AT-YL	255/55R18	XL	109H	BSW	2271	8J	10.43	29.02	50	13	500 A B
SUV-3802-AT-YL	255/60R18	XL	112H	BSW	2469	7 1/2J	10.24	30.04	50	13	500 A B
SUV-3803-AT-YL	265/70R18	STD	116S	BSW	2756	8J	10.71	32.64	44	13	500 A B
SUV-3804-AT-YL	275/65R18	STD	116S	BSW	2756	8J	10.98	32.09	44	13	500 A B
SUV-3209-AT-YL	305/50R20	XL	120T	BSW	3086	9 1/2J	12.44	32.05	44	13	500 A B
LTR-3508-AT-YL	30x9.50R15LT	C	104S	BSW	1984	7 1/2J	9.45	29.53	51	16	500 A B
LTR-3509-AT-YL	33x12.50R15LT	C	108S	BSW	2205	10J	12.50	32.52	36	16	500 A B
LTR-3510-AT-YL	35x12.50R15LT	C	113Q	BSW	2535	10J	12.52	34.53	36	16	500 A B
LTR-3511-AT-YL	LT235/75R15	C	104/101S	BSW	1984/1819	6 1/2J	9.25	29.09	51	16	500 A B
LTR-3609-AT-YL	LT225/70R16	C	102/99S	BSW	1874/1709	6 1/2J	8.98	28.43	51	16	500 A B
LTR-3610-AT-YL	LT245/75R16	E	120/116Q	BSW	3086/2756	7J	9.76	30.47	80	16	500 A B
LTR-3611-AT-YL	LT265/70R16	D	117/114S	BSW	2756/2601	8J	10.71	30.63	65	16	500 A B
LTR-3612-AT-YL	LT265/75R16	D	119/116Q	BSW	2998/2756	7 1/2J	10.51	31.65	65	16	500 A B
LTR-3613-AT-YL	LT265/75R16	E	123/120Q	BSW	3417/3086	7 1/2J	10.51	31.65	80	16	500 A B
LTR-3614-AT-YL	LT285/75R16	D	122/119R	BSW	3307/2998	8J	10.51	31.65	65	16	500 A B
LTR-3615-AT-YL	LT285/75R16	D	126/123Q	BSW	3748/3417	8J	11.26	32.83	65	16	500 A B
LTR-3710-AT-YL	LT235/80R17	D	120/117R	BSW	3086/2833	6 1/2J	9.25	31.81	65	16	500 A B
LTR-3711-AT-YL	LT285/70R17	D	121/118R	BSW	3197/2910	8 1/2J	11.50	32.76	65	16	500 A B
LTR-3712-AT-YL	LT305/70R17	D	119/116Q	BSW	3000/2755	9J	12.24	33.86	51	16	500 A B
LTR-3713-AT-YL	LT315/70R17	E	121/118R	BSW	3195/2910	9 1/2J	12.72	34.41	51	16	500 A B
LTR-3805-AT-YL	LT275/65R18	E	123/120S	BSW	3417/3086	8J	10.98	32.09	80	16	500 A B
LTR-3806-AT-YL	LT285/65R18	E	121/118R	BSW	3638/3307	8 1/2J	11.50	32.56	80	16	500 A B
LTR-3807-AT-YL	LT325/65R18	D	121/118S	BSW	3195/2910	9 1/2J	13.03	34.61	65	16	500 A B
LTR-3210-AT-YL	LT305/55R20	D	121/118S	BSW	3197/2910	9 1/2J	12.44	33.23	65	16	500 A B
LTR-3211-AT-YL	LT325/60R20	E	126/123S	BSW	3750/3415	9 1/2J	13.03	35.35	65	16	500 A B

• Gray part is AVAILABLE IN 2017.



## MAGA A/T TWO

- Special joints between tread blocks reduce excessive flex for better traction and steering response on and off road.
- Deep sipes and slanted voids effectively channel away water.
- The lugs on the shoulder are staggered to improve traction in deep sand and loose dirt.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
SUV-3616-AT-YL	265/70R16	STD	112T	BSW	2469	8J	10.71	30.63	44	13	460 A A
SUV-3715-AT-YL	265/65R17	STD	112T	BSW	2756	8J	10.71	30.55	44	13	460 A A
SUV-3714-AT-YL	265/70R17	STD	115S	BSW	2679	8J	10.71	31.65	44	13	460 A A
SUV-3716-AT-YL	285/70R17	STD	117S	BSW	2833	8½J	11.50	32.76	44	13	-
SUV-3813-AT-YL	285/60R18	XL	120S	BSW	3086	8½J	11.50	31.46	50	13	460 A A
SUV-3814-AT-YL	305/60R18	STD	120S	BSW	3086	9J	12.24	32.40	44	13	460 A A
SUV-3004-AT-YL	265/50R20	XL	111S	BSW	2403	8½J	10.91	30.47	50	13	-
SUV-3001-AT-YL	275/55R20	XL	117S	BSW	2833	8½J	11.18	31.89	50	13	460 A A
SUV-3002-AT-YL	285/55R20	STD	115S	BSW	2679	9J	11.69	32.36	50	13	-
SUV-3003-AT-YL	285/55R20	XL	119S	BSW	2998	9J	11.69	32.36	50	13	-
SUV-3006-AT-YL	305/50R20	XL	120S	BSW	3086	9½J	12.44	32.05	50	13	460 A A
LTR-3617-AT-YL	LT265/75R16	E	123/120Q	BSW	3417/3086	7½J	10.51	31.65	80	16	-
LTR-3618-AT-YL	LT285/75R16	E	126/123Q	BSW	3748/3417	8J	11.26	32.83	80	16	-
LTR-3719-AT-YL	LT285/70R17	E	121/118Q	BSW	3195/2910	8½J	11.50	32.76	65	16	-
LTR-3810-AT-YL	LT285/60R18	E	122/119Q	BSW	3306/2998	8½J	11.50	31.46	80	16	-
LTR-3809-AT-YL	LT325/60R18	E	124/121Q	BSW	3525/3195	9½J	13.03	33.35	65	16	-
LTR-3808-AT-YL	LT325/65R18	E	127/124Q	BSW	3195/2910	9½J	13.03	34.61	50	16	-
SUV-3008-AT-YL	295/60R20	STD	116S	BSW	2755	8½J	11.77	33.94	44	13	460 A A
LTR-3718-AT-YL	LT295/70R17	E	121/118Q	BSW	3195/2910	8½J	11.77	33.31	80	16	-
LTR-3720-AT-YL	LT305/70R17	E	121/118R	BSW	3195/2910	9J	12.24	33.86	65	16	-
LTR-3816-AT-YL	LT275/70R18	E	125/122Q	BSW	3640/3305	8J	10.98	33.19	80	16	-
LTR-3811-AT-YL	LT285/65R18	E	125/122R	BSW	3640/3305	8½J	11.50	32.56	80	16	-
LTR-3815-AT-YL	LT295/70R18	E	129/126Q	BSW	4080/3750	8½J	11.77	34.29	80	16	-
LTR-3005-AT-YL	LT305/55R20	E	121/118S	BSW	3195/2910	9½J	12.44	33.23	65	16	-
LTR-3007-AT-YL	LT325/60R20	D	126/123Q	BSW	3195/2910	9½J	13.03	35.35	51	16	-
LTR-3212-AT-YL	LT285/55R22	E	124/121R	BSW	3525/3195	9J	11.69	32.36	80	16	-
LTR-3213-AT-YL	LT325/50R22	E	122R	BSW	3305	10J	13.23	34.84	65	16	-

• Gray part is AVAILABLE IN 2017.

## DIAS ZERO

- The 'leaf' pattern utilizes slanted grooves to add additional water drainage on wet ground.
- The continuous central rib helps maintain stability in straight-line driving.
- Wear resistant compound is used to deliver a longer life.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
UHP-3010-YL	275/40R20	XL	106W	BSW	2094	9½J	10.94	28.66	50	10	300 A A
UHP-3011-YL	275/40R20	XL	106V	BSW	2094	9½J	10.94	28.66	50	10	300 A A
UHP-3012-YL	275/45R20	XL	110V	BSW	2337	9.0J	10.75	28.78	50	10	300 A A
SUV-3013-YL	275/55R20	XL	117V	BSW	2833	8½J	11.18	31.89	50	10	300 A A
SUV-3014-YL	275/60R20	XL	119V	BSW	2679	8½J	10.98	32.99	50	10	300 A A
SUV-3015-YL	275/60R20	XL	119H	BSW	2679	8½J	10.98	32.99	50	10	300 A A
UHP-3223-YL	265/35R22	XL	102W	BSW	1874	9½J	10.67	29.33	50	10	300 A A
UHP-3224-YL	265/40R22	XL	106V	BSW	2094	9½J	10.67	30.35	50	10	300 A A
UHP-3225-YL	305/40R22	XL	114V	BSW	2601	11J	12.32	31.61	50	10	300 A A
UHP-3016-YL	285/50R20	XL	116V	BSW	2756	9J	11.69	31.26	50	10	300 A A
UHP-3017-YL	295/45R20	XL	114W	BSW	2601	10J	11.65	32.48	50	10	300 A A
UHP-3226-YL	285/35R22	XL	106W	BSW	2094	10J	11.42	29.88	50	10	300 A A
UHP-3227-YL	295/30R22	XL	103W	BSW	1929	10½J	11.85	29.02	50	10	300 A A
UHP-3422-YL	275/25R24	XL	96W	BSW	1565	10J	11.14	29.45	50	10	300 A A
UHP-3423-YL	295/35R24	XL	110W	BSW	2337	10½J	11.85	32.13	50	10	300 A A
UHP-3424-YL	295/35R24	XL	110V	BSW	2337	10½J	11.85	32.13	50	10	300 A A
UHP-3425-YL	305/35R24	XL	112W	BSW	2469	11J	12.32	32.44	50	10	300 A A
UHP-3426-YL	305/35R24	XL	112V	BSW	2469	11J	12.32	32.44	50	10	300 A A

• Gray part is AVAILABLE IN 2017.





## DRAK M/T

- The high turn-up sidewall construction increases puncture resistance.
- The balanced void ratio efficiently removes mud and dirt to provide continuous off-road traction.

Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)
LTR-3501-MT-YL	31x10.50R15LT	C	109Q	BSW	2270	8 1/2J	10.54	30.52	50	19
LTR-3504-MT-YL	32x11.50R15LT	C	113Q	BSW	2535	9J	11.42	31.52	50	19
LTR-3505-MT-YL	33x12.50R15LT	C	108Q	BSW	2205	10J	12.50	32.52	35	20
LTR-3701-MT-YL	33x12.50R17LT	E	120Q	BSW	3085	10J	12.50	32.52	65	20
LTR-3502-MT-YL	LT215/75R15	C	100/97Q	BSW	1765/1610	6J	8.50	27.68	50	17
LTR-3503-MT-YL	LT235/75R15	C	104/101Q	BSW	1985/1820	6 1/2J	9.23	28.86	50	17
LTR-3604-MT-YL	LT215/85R16	E	115/112Q	BSW	2680/2470	6J	8.50	30.39	80	17
LTR-3602-MT-YL	LT225/75R16	E	115/112N	BSW	2680/2470	6J	8.78	29.29	80	17
LTR-3605-MT-YL	LT235/85R16	E	120/116Q	BSW	3042/2778	6 1/2J	9.25	31.73	80	17
LTR-3603-MT-YL	LT245/75R16	E	120/116N	BSW	3042/2778	7J	9.76	30.47	80	17
LTR-3606-MT-YL	LT265/75R16	E	123/120Q	BSW	3415/3085	7 1/2J	10.51	31.65	80	18
LTR-3607-MT-YL	LT285/75R16	E	126/123Q	BSW	3750/3415	8J	11.26	32.83	80	18
LTR-3601-MT-YL	LT305/70R16	E	124/121P	BSW	3525/3195	9J	12.24	32.83	80	19
LTR-3608-MT-YL	LT315/75R16	E	127/124Q	BSW	3195/2910	8 1/2J	12.32	34.57	50	18
SUV-3901-MT-YL	255/55R19	XL	111R	BSW	2403	8J	10.43	30.04	50	16
SUV-3203-MT-YL	285/50R20	XL	115T	BSW	2756	9J	11.69	31.26	50	16
LTR-3703-MT-YL	35x12.50R17LT	E	125P	BSW	3195	10J	12.50	34.52	65	20
LTR-3705-MT-YL	37x13.50R17LT	D	121P	BSW	3195	11J	13.58	36.52	50	20
LTR-3803-MT-YL	33x12.50R18LT	E	118Q	BSW	2910	10J	12.50	32.52	65	20
LTR-3801-MT-YL	35x12.50R18LT	E	123Q	BSW	3415	10J	12.50	34.52	65	20
LTR-3804-MT-YL	37x13.50R18LT	D	124P	BSW	3525	11J	13.58	36.52	50	20
LTR-3002-MT-YL	33x12.50R20LT	E	114Q	BSW	2600	10J	12.50	32.52	65	20
LTR-3001-MT-YL	35x12.50R20LT	E	121Q	BSW	3195	10J	12.50	34.52	65	20
LTR-3007-MT-YL	35x15.50R20LT	E	121Q	BSW	3195	10J	12.50	34.52	65	18
LTR-3003-MT-YL	37x13.50R20LT	E	127Q	BSW	3860	11J	13.58	36.52	65	20
LTR-3201-MT-YL	37x13.50R22LT	E	123Q	BSW	3415	11J	13.58	36.52	65	20
LTR-3609-MT-YL	LT265/75R16	E	123/120N	BSW	3415/3085	7 1/2J	10.51	30.67	80	18
LTR-3610-MT-YL	LT285/75R16	E	122/119N	BSW	3750/3415	8J	11.26	33.07	80	18
LTR-3704-MT-YL	LT285/70R17	E	121/118Q	BSW	3195/2910	8 1/2J	11.50	32.76	80	18
LTR-3702-MT-YL	LT295/70R17	E	121/118P	BSW	3195/2910	8 1/2J	11.77	33.31	80	18
LTR-3802-MT-YL	LT295/70R18	E	129/126Q	BSW	4080/3750	8 1/2J	11.77	34.29	80	18
LTR-3006-MT-YL	LT285/55R20	E	122/119Q	BSW	3305/3000	9J	11.69	32.36	80	18
LTR-3004-MT-YL	LT295/60R20	E	126/123Q	BSW	3750/3415	8 1/2J	11.77	33.94	80	20
LTR-3005-MT-YL	LT295/65R20	E	129/126Q	BSW	4080/3750	8 1/2J	11.77	35.12	80	18
LTR-3202-MT-YL	LT325/50R22	E	122Q	BSW	3305	10J	13.23	34.84	65	18

• Gray part is AVAILABLE IN 2017.

## MAHO 77

- 3D sipes on tread to enhance the gripping power.
- Fully considering the drive and ride comfort.
- Wear resistant compound is used to deliver a longer life.



Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
PCR-3504-HT-YL	205/70R15	STD	96H	BSW	1499	6J	8.23	26.34	44	11	500 A B
PCR-3505-HT-YL	205/70R15	XL	100H	BSW	1764	6J	8.23	26.34	50	11	500 A B
SUV-3508-HT-YL	215/70R15	STD	98H	BSW	1620	6 1/2J	8.70	26.89	44	11	500 A B
SUV-3501-HT-YL	215/75R15	STD	100H	BSW	1742	6J	8.50	27.68	44	11	500 A B
SUV-3509-HT-YL	225/70R15	STD	100H	BSW	1753	6 1/2J	8.98	27.44	44	11	500 A B
SUV-3506-HT-YL	225/75R15	STD	102H	BSW	1874	6J	8.78	28.31	44	11	500 A B
SUV-3510-HT-YL	235/70R15	XL	107H	BSW	2149	7J	9.45	27.99	50	11	500 A B
SUV-3502-HT-YL	235/75R15	STD	105H	BSW	2028	6 1/2J	9.25	28.86	44	11	500 A B
SUV-3503-HT-YL	235/75R15	XL	109H	BSW	2183	6 1/2J	9.25	28.86	50	11	500 A B
SUV-3511-HT-YL	255/60R15	STD	102T	BSW	1885	7 1/2J	10.24	27.05	44	11	500 A B
SUV-3512-HT-YL	255/70R15	STD	108H	BSW	2183	7 1/2J	10.24	29.09	44	11	500 A B
SUV-3507-HT-YL	265/70R15	STD	112H	BSW	2337	8J	10.71	29.65	44	11	500 A B
PCR-3622-HT-YL	205/60R16	STD	92H	BSW	1356	6J	8.23	25.67	44	11	500 A B
PCR-3624-HT-YL	205/65R16	STD	95H	BSW	1477	6J	8.23	26.46	44	11	500 A B
PCR-3615-HT-YL	215/60R16	STD	95H	BSW	1477	6 1/2J	8.70	26.14	44	11	500 A B
PCR-3616-HT-YL	215/60R16	XL	99H	BSW	1709	6 1/2J	8.70	26.14	50	11	500 A B
SUV-3603-HT-YL	215/65R16	STD	98H	BSW	1565	6 1/2J	8.70	27.01	44	11	500 A B
SUV-3604-HT-YL	215/65R16	XL	102H	BSW	1874	6 1/2J	8.70	27.01	50	11	500 A B
SUV-3606-HT-YL	215/70R16	STD	100H	BSW	1709	6 1/2J	8.70	27.87	44	11	500 A B
SUV-3617-HT-YL	225/60R16	STD	98H	BSW	1609	6 1/2J	8.98	26.61	44	11	500 A B
SUV-3618-HT-YL	225/65R16	STD	100H	BSW	1709	6 1/2J	8.98	27.48	44	11	500 A B
SUV-3605-HT-YL	225/70R16	STD	103H	BSW	1819	6 1/2J	8.98	28.43	44	11	500 A B
SUV-3610-HT-YL	225/75R16	STD	104T	BSW	1984	6J	8.78	29.29	44	11	500 A B
SUV-3608-HT-YL	235/60R16	STD	100H	BSW	1709	7J	9.45	27.09	44	11	500 A B
SUV-3619-HT-YL	235/65R16	STD	103H	BSW	1819	7J	9.45	28.03	44	11	500 A B
SUV-3601-HT-YL	235/70R16	STD	106H	BSW	1984	7J	9.45	28.98	44	11	500 A B
SUV-3634-HT-YL	235/75R16	XL	112T	BSW	2271	6 1/2J	9.25	29.84	50	11	500 A B
SUV-3611-HT-YL	245/70R16	XL	111H	BSW	2403	7J	9.76	29.53	50	11	500 A B
SUV-3620-HT-YL	245/75R16	STD	111H	BSW	2271	7J	9.76	30.47	44	11	500 A B





# MAHO 77

Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
SUV-3609-HT-YL	255/65R16	STD	109H	BSW	2094	7 1/2J	10.24	29.06	44	11	500 A B
SUV-3602-HT-YL	255/70R16	STD	111H	BSW	2271	7 1/2J	10.24	30.08	44	11	500 A B
SUV-3607-HT-YL	265/70R16	STD	112H	BSW	2403	8J	10.71	30.63	44	11	500 A B
SUV-3612-HT-YL	265/75R16	STD	116H	BSW	2601	7 1/2J	10.51	31.65	44	11	500 A B
SUV-3613-HT-YL	265/75R16	STD	114T	BSW	2601	7 1/2J	10.51	31.65	44	11	500 A B
SUV-3623-HT-YL	275/60R16	STD	109T	BSW	2271	8J	10.98	28.97	44	11	500 A B
SUV-3621-HT-YL	275/70R16	STD	114H	BSW	2601	8J	10.98	31.18	44	11	500 A B
PCR-3701-HT-YL	215/60R17	STD	96H	BSW	1521	6 1/2J	8.70	27.17	44	11	500 A B
PCR-3702-HT-YL	215/60R17	XL	100H	BSW	1764	6 1/2J	8.70	27.17	50	11	500 A B
SUV-3731-HT-YL	215/65R17	STD	99H	BSW	1708	6 1/2J	8.70	28.03	44	11	500 A B
SUV-3732-HT-YL	215/65R17	STD	99V	BSW	1708	6 1/2J	8.70	28.03	44	11	500 A B
SUV-3709-HT-YL	225/65R17	STD	102H	BSW	1764	6 1/2J	8.98	28.50	44	11	500 A B
SUV-3722-HT-YL	225/60R17	STD	99H	BSW	1653	6 1/2J	8.98	27.64	44	11	500 A B
SUV-3723-HT-YL	225/60R17	XL	103H	BSW	1929	6 1/2J	8.98	27.64	50	11	500 A B
SUV-3714-HT-YL	225/70R17	XL	108T	BSW	2205	6 1/2J	8.98	29.45	50	11	500 A B
SUV-3705-HT-YL	235/65R17	XL	108H	BSW	2205	7J	9.45	29.06	50	11	500 A B
SUV-3710-HT-YL	235/60R17	STD	102H	BSW	1764	7J	9.45	28.11	44	11	500 A B
SUV-3706-HT-YL	235/70R17	XL	109H	BSW	2039	7J	9.45	30.00	44	11	500 A B
SUV-3724-HT-YL	235/75R17	STD	109S	BSW	2205	6 1/2J	9.25	30.87	44	11	500 A B
SUV-3704-HT-YL	245/65R17	XL	111H	BSW	2403	7J	9.76	29.53	50	11	500 A B
SUV-3721-HT-YL	245/70R17	STD	110H	BSW	2205	7J	9.76	30.55	44	11	500 A B
SUV-3719-HT-YL	255/60R17	STD	106V	BSW	2039	7 1/2J	10.24	29.06	44	11	500 A B
SUV-3720-HT-YL	255/60R17	XL	110V	BSW	2337	7 1/2J	10.24	29.06	50	11	500 A B
SUV-3715-HT-YL	255/65R17	STD	110H	BSW	2205	7 1/2J	10.24	30.08	44	11	500 A B
SUV-3716-HT-YL	255/65R17	XL	114H	BSW	2601	7 1/2J	10.24	30.08	50	11	500 A B
SUV-3717-HT-YL	255/70R17	STD	112T	BSW	2337	7 1/2J	10.24	31.10	44	11	500 A B
SUV-3707-HT-YL	265/65R17	STD	112H	BSW	2337	8J	10.71	30.55	44	11	500 A B
SUV-3708-HT-YL	265/65R17	XL	116H	BSW	2756	8J	10.71	30.55	50	11	500 A B
SUV-3703-HT-YL	265/70R17	STD	115H	BSW	2535	8J	10.71	31.65	44	11	500 A B
SUV-3718-HT-YL	275/60R17	STD	110H	BSW	2337	8J	10.98	30.00	44	11	500 A B
SUV-3712-HT-YL	275/65R17	STD	115H	BSW	2535	8J	10.98	31.10	44	11	500 A B
SUV-3713-HT-YL	275/65R17	XL	119H	BSW	3000	8J	10.98	31.10	50	11	500 A B
SUV-3711-HT-YL	285/65R17	STD	116H	BSW	2679	8 1/2J	11.50	31.57	44	11	500 A B
SUV-3803-HT-YL	225/60R18	XL	104H	BSW	1984	6 1/2J	8.98	28.62	50	11	500 A B
SUV-3804-HT-YL	225/65R18	STD	103H	BSW	1929	6 1/2J	8.98	29.49	44	11	500 A B
SUV-3801-HT-YL	235/60R18	STD	103H	BSW	1874	7J	9.45	29.09	44	11	500 A B
SUV-3802-HT-YL	235/60R18	XL	107H	BSW	2149	7J	9.45	29.09	50	11	500 A B
SUV-3814-HT-YL	235/65R18	STD	106H	BSW	1984	7J	9.45	30.04	44	11	500 A B
SUV-3815-HT-YL	235/65R18	XL	110H	BSW	2337	7J	9.45	30.04	50	11	500 A B
SUV-3809-HT-YL	245/60R18	STD	105H	BSW	1984	7J	9.76	29.57	44	11	500 A B
SUV-3811-HT-YL	255/60R18	XL	112V	BSW	2469	7 1/2J	10.24	30.04	50	11	500 A B
SUV-3810-HT-YL	255/70R18	STD	113H	BSW	2469	7 1/2J	10.24	32.09	44	11	500 A B

# MAHO 77

Item Code	Size	Load Range/ Ply Rating	Load Index/ Speed rating	Sidewall	MaxLoad (lbs)	Rim Width (in)	Section Width (in)	Overall Diameter (in)	Max PSI (Cold)	Tread Depth (32ND)	UTQG
SUV-3806-HT-YL	265/60R18	STD	110H	BSW	2271	8J	10.71	30.51	44	11	500 A B
SUV-3807-HT-YL	265/60R18	XL	114H	BSW	2601	8J	10.71	30.51	50	11	500 A B
SUV-3808-HT-YL	265/65R18	STD	114H	BSW	2469	8J	10.71	31.54	44	11	500 A B
SUV-3812-HT-YL	265/70R18	STD	116H	BSW	2601	8J	10.71	32.64	44	11	500 A B
SUV-3813-HT-YL	275/65R18	STD	116H	BSW	2601	8J	10.98	32.09	44	11	500 A B
SUV-3816-HT-YL	P275/70R18	STD	116H	BSW	2756	8J	10.98	33.19	44	11	500 A B
SUV-3805-HT-YL	285/60R18	XL	120H	BSW	3085	8 1/2J	11.50	31.46	50	11	500 A B
SUV-3903-HT-YL	245/55R19	STD	103W	BSW	1929	7 1/2J	9.96	29.65	44	11	500 A B
SUV-3901-HT-YL	255/50R19	XL	107V	BSW	2149	8J	10.43	29.09	50	11	500 A B
SUV-3902-HT-YL	255/55R19	XL	111V	BSW	2403	8J	10.43	30.04	50	11	500 A B
SUV-3004-HT-YL	275/55R20	XL	117H	BSW	2833	8 1/2J	11.18	31.89	50	11	500 A B
SUV-3001-HT-YL	275/60R20	STD	115V	BSW	2601	8J	10.98	32.99	44	11	500 A B
SUV-3002-HT-YL	275/60R20	XL	117H	BSW	-	-	-	-	-	11	500 A B
LTR-3513-HT-YL	LT215/75R15	C	100/97T	BSW	1765/1610	6J	8.50	27.68	50	13	-
LTR-3514-HT-YL	LT225/75R15	C	102/99T	BSW	1875/1710	6J	8.78	28.31	50	13	-
LTR-3515-HT-YL	LT235/75R15	C	104/101Q	BSW	1985/1820	6 1/2J	9.23	28.86	50	13	-
LTR-3632-HT-YL	LT215/85R16	E	115/112Q	BSW	2680/2470	6J	8.50	30.39	80	13	-
LTR-3626-HT-YL	LT225/70R16	C	102/99S	BSW	1875/1710	6 1/2J	8.98	28.43	50	13	-
LTR-3629-HT-YL	LT225/75R16	E	115/112N	BSW	2680/2470	6J	8.78	29.29	80	13	-
LTR-3625-HT-YL	LT235/85R16	E	120/116Q	BSW	3042/2778	6 1/2J	9.25	31.73	80	13	-
LTR-3633-HT-YL	LT245/70R16	E	113/110S	BSW	2910/2680	7J	9.76	29.53	80	13	-
LTR-3614-HT-YL	LT245/75R16	E	120/116S	BSW	3042/2778	7J	9.76	30.47	80	13	-
LTR-3627-HT-YL	LT265/70R16	E	110/107S	BSW	3195/2910	8J	10.71	30.63	80	13	-
LTR-3630-HT-YL	LT265/75R16	E	123/120N	BSW	3415/3085	7 1/2J	10.51	30.67	80	13	-
LTR-3631-HT-YL	LT285/75R16	E	126/123Q	BSW	3750/3415	8J	11.26	32.83	80	13	-
LTR-3628-HT-YL	LT305/70R16	E	118/115S	BSW	3525/3195	9J	12.24	32.83	65	13	-
LTR-3730-HT-YL	LT235/80R17	E	120/117S	BSW	3085/2835	6 1/2J	9.25	31.81	80	13	-
LTR-3729-HT-YL	LT245/70R17	E	119/116S	BSW	3000/2755	7J	9.76	30.55	80	13	-
LTR-3728-HT-YL	LT245/75R17	E	121/118S	BSW	3195/2910	7J	9.76	31.50	80	13	-
LTR-3725-HT-YL	LT265/70R17	E	121/118S	BSW	3195/2910	8J	10.71	31.65	80	13	-
LTR-3727-HT-YL	LT285/70R17	E	121/118S	BSW	3195/2910	8 1/2J	11.50	32.76	80	13	-
LTR-3726-HT-YL	LT315/70R17	E	121/118S	BSW	3195/2910	9 1/2J	12.72	34.41	65	13	-
LTR-3003-HT-YL	LT275/65R20	E	126/123Q	BSW	3750/3415	8J	10.98	34.09	80	13	-

• Gray part is AVAILABLE IN 2017.



# GR612

## GR612 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- Steer response.
- Resistance to shoulder edge wear.
- Wet handling.
- Strong wear resistant.
- Stone reject character design.



Economy



Good handling



Comfort

GR612 suitable for Long Haul road



# GR622

## GR622 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- Excellent traction and wet weather handling.
- Optimized tread design and tread depth for long life.



Economy



Good handling



Comfort

GR622 suitable for Long Haul road



Item Code	Size	Ply Rating	Load Index	Speed Symbol	Overall Diameter (Inch)	Section Width (Inch)	Rim Width	Max Load Single/Dual (lbs)	Max Pressurer (psi)	Tread Depth (32nds)
MTR-3101-YL	11R22.5	14	144/142	M	41.3	11.0	8.25	6175/5840	105	18
MTR-3102-YL	11R22.5	16	146/143	M	41.3	11.0	8.25	6610/6005	120	18
MTR-3103-YL	11R24.5	14	146/143	M	43.2	11.0	8.25	6610/6005	105	18
MTR-3104-YL	11R24.5	16	149/146	M	43.2	11.0	8.25	7160/6610	120	18
MTR-3107-YL	295/75R22.5	14	144/141	M	39.8	11.7	9	6175/5675	110	18
MTR-3105-YL	285/75R24.5	14	144/141	M	41.3	11.1	8.25	6175/5675	110	18
MTR-3117-YL	255/70R22.5	16	140/137	M	36.5	10	7.5	5510/5070	116	18
MTR-3109-YL	215/75R17.5	18	135/133	J	30.2	8.3	6	4805/4540	125	15
MTR-3110-YL	235/75R17.5	18	143/141	J	31.2	9.2	6.75	6005/5675	130	15
MTR-3116-YL	225/70R19.5	14	128/126	M	32.1	8.9	6.75	3970/3750	110	15
MTR-3112-YL	245/70R19.5	16	136/134	M	33.1	9.8	7.5	4940/4680	120	15
MTR-3113-YL	265/70R19.5	16	140/138	M	34.2	10.3	7.5	5510/5200	115	15
MTR-3115-YL	275/70R22.5	16	144/141	M	37.5	10.9	8.25	6175/5675	110	18
MTR-3114-YL	275/70R22.5	18	148/145	M	37.5	10.9	8.25	6945/6395	125	18

Item Code	Size	Ply Rating	Load Index	Speed Symbol	Overall Diameter (Inch)	Section Width (Inch)	Rim Width	Max Load Single/Dual (lbs)	Max Pressurer (psi)	Tread Depth (32nds)
MTR-3201-YL	11R22.5	14	144/142	M	41.8	11.0	8.25	6175/5840	105	26
MTR-3202-YL	11R22.5	16	146/143	M	41.8	11.0	8.25	6610/6005	120	26
MTR-3203-YL	11R24.5	14	146/143	M	43.8	11.0	8.25	6610/6005	105	26
MTR-3204-YL	11R24.5	16	149/146	M	43.8	11.0	8.25	7160/6610	120	26
MTR-3207-YL	295/75R22.5	14	144/141	M	40.4	11.7	9.00	6175/5675	110	26
MTR-3205-YL	285/75R24.5	14	144/141	M	41.9	11.1	8.25	6175/5675	110	26



# GR636

## GR636 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- Wide tread for long life.
- More suitable design for long distance and standard loading condition.
- Design for trailer position only.



Economy



Good handling



Comfort

GR636 suitable for Long Haul road



Item Code	Size	Ply Rating	Load Index	Speed Symbol	Overall Diameter (Inch)	Section Width (Inch)	Rim Width	Max Load Single/Dual (lbs)	Max Pressurer (psi)	Tread Depth (32nds)
MTR-3301-YL	11R22.5	14	144/142	M	41.0	11.0	8.25	6175/5840	105	14
MTR-3302-YL	11R22.5	16	146/143	M	41.0	11.0	8.25	6610/6005	120	14
MTR-3303-YL	11R24.5	14	146/143	M	43.0	11.0	8.25	6610/6005	105	14
MTR-3304-YL	11R24.5	16	149/146	M	43.0	11.0	8.25	7160/6610	120	14
MTR-3307-YL	295/75R22.5	14	144/141	M	39.6	11.7	9.00	6175/5675	110	14
MTR-3305-YL	285/75R24.5	14	144/141	M	41.1	11.1	8.25	6175/5675	110	14

# GR662

## GR662 MAIN TRAIT

- High way and long distance use.
- Fuel efficient with lower rolling resistance steer tyre.
- Excellent heat resistance performance .
- Low noisy.



Economy



Good handling



Comfort

GR662 suitable for Regional road



Item Code	Size	Ply Rating	Load Index	Speed Symbol	Overall Diameter (Inch)	Section Width (Inch)	Rim Width	Max Load Single/Dual (lbs)	Max Pressurer (psi)	Tread Depth (32nds)
MTR-3401-YL	315/80R22.5	20	156/150	M	42.5	12.3	9.00	8820/7385	125	20

# GR666

## GR666 MAIN TRAIT

- Fuel efficient with lower rolling resistance.
- High way use for trailer.
- No compromise on durability, irregular wear resistance and wet performance.
- Ride comfort & easy handling.



Economy



Good handling



Comfort

GR666 suitable for Regional road



Item Code	Size	Ply Rating	Load Index	Speed Symbol	Overall Diameter (Inch)	Section Width (Inch)	Rim Width	Max Load Single/Dual (lbs)	Max Pressurer (psi)	Tread Depth (32nds)
MTR-3501-YL	385/65R22.5	20	160/	K	42.0	15.3	11.75	9920/	130	19

# GR678

## GR678 MAIN TRAIT

- Fuel efficient drive tyre.
- No compromise on durability, irregular wear resistance and wet performance.
- Excellent traction and wet weather handling.
- High mileage in low severity operations.



Economy



Good handling



Comfort

GR678 suitable for Regional road



Item Code	Size	Ply Rating	Load Index	Speed Symbol	Overall Diameter (Inch)	Section Width (Inch)	Rim Width	Max Load Single/Dual (lbs)	Max Pressurer (psi)	Tread Depth (32nds)
MTR-3601-YL	225/70R19.5	14	128/126	M	32.1	8.9	6.75	3970/3750	110	19
MTR-3602-YL	245/70R19.5	16	136/134	M	33.3	9.8	7.50	4940/4680	120	19
MTR-3603-YL	265/70R19.5	16	140/138	M	34.4	10.3	7.50	5510/5200	115	19